

# Product Specifications




## LMR200 COAXIAL CABLE



### Standard

- GY/T 135—1998
- GB/T14864
- ROHS 2011/65/EU



### Application

- RF signal transmission
- MATV, CATV, CCTV
- Digital video applications
- Drop in broadcast
- Satellite systems

### Specification

- |                   |                 |                                |
|-------------------|-----------------|--------------------------------|
| ■ Inner Conductor | BC/CCS          | $\Phi 1.12 \pm 0.01 \text{mm}$ |
| ■ Insulation      | Foam PE         | $\Phi 2.95 \pm 0.05 \text{mm}$ |
| ■ Aluminum Mylar  | Al Foil         |                                |
| ■ Braiding        | 50%-95%AL/BC/TC |                                |
| ■ Jelly           | Yes/No          |                                |
| ■ Outer Sheath    | PVC             | $\Phi 4.95 \pm 0.05 \text{mm}$ |

### Electrical Performance (20 °C)

- |   |                                |
|---|--------------------------------|
| ■ Impedance: $50 \pm 3 \text{ Ohm}$     | ■ Sparker Test: 4000VAC        |
| ■ Capacitance: $80.3 \pm 3 \text{pF/m}$ | ■ Velocity Of Propagation: 83% |
| ■ Return Loss: 20dB min (5-2300MHz)     |                                |



# Product Specifications

## *Electrical Characteristics (20 °C)*

---

Frequency (MHz)	30	50	150	220	450	900	1500	1800	2000	2500	5800
Maximum (dB/100ft)	1.8	2.3	4.0	4.8	7.0	9.9	12.9	14.2	15.0	16.9	26.4
Maximum (dB/100m)	5.8	7.5	13.1	15.9	22.8	32.6	42.4	46.6	49.3	55.4	86.5

## *Thermal Characteristics*

---

- For fixed installation: -20°C up to +60°C
- For mobile installation: 0°C up to +50°C